

NOTES:


DRAWING NO.


1. SUFFIX "X" INDICATES HANDLE/PLUG COLOR OPTIONS.

R-RED, B-BLUE, Y -YELLOW, W-WHITE

- 2. CRITICAL DIMENSIONS ARE CIRCLED AND SUBJECT TO INSPECTION. DIMENSIONS IN PARENTHESES ARE FOR REFERENCE ONLY.
- 3. ALL DIMENSIONS ARE IN INCHES, WITH NOMINAL DIMENSIONS IN METRIC BELOW.
- 4. FEMALE LUER COFORMS WITH ISO594-2.
- 5. MALE LUER CONFORMS TO ISO594-2.
- 6. FEMALE SWABABLE LUER COMPATIBLE WITH ISO594-2, AND ISO80369-7.
- 7. MATERIAL: ALL MATERIALS ARE GAMMA RESISTANT, MEET USP CLASS VI; ARE DEHP FREE, AND NOT MADE WITH NATURAL RUBBER LATEX.

REVISION HISTORY								
REV	DESCRIPTION (ECO)	DATE	APPROVED					
С	UPDATE LATEX NOTE ECO 6082	5/29/14	AK					
D	ADD ISO80369-7 TO NOTES. ECO 8017	05/03/18	AK					





QUALITY CRITERIA:

O.D. FLASH: 0.02 MAX. (0.5mm)

GATE VESTIGE: 0.01 MAX. (0.3mm)

EMBEDDED PARTICLES, BUBBLES, SPOTS, STAINS: 0.3mm² MAX. NO MORE THAN 3 PER PART.

	DRAWN BY	S.Rogier	DATE 6/24/2	014	HR®	Halkey-Robert	R
	APPROVED BY		DATE		ПП	naikey-kobeit	3
	MATERIAL	·			.E		
	FINISH				4-way S	Wabable Stopcock tee Handle as	SSY.
-	UNLESS OTHERWISE	SPECIFIED:	THIRD ANGLE PROJEC	TION SIZE	DRAWING	S NO. 00 4 T 00 4 00 4 V	REV
RTY	DIMENSIONS ARE IN I	NCHES		A	\	C245824024X	D

MOLDED PARTS: GATES, PARTING LINES, AND FLASH PER QUALITY CRITERIA

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS SOLE PROPERT
OF HALKEY-ROBERTS CORPORATION ST. PETERSBURG, FL. ANY
REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN
PERMISSION OF HALKEY-ROBERTS CORPORATION IS PROHIBITED.

DIMENSIONS ARE IN INCHES
TOLERANCES:
ANGULAR: ± 1°
TWO PLACE DECIMAL ± .01
THREE PLACE DECIMAL ± .005

A C245824024X

SCALE DO NOT SCALE DRAWING SHEE

1 OF 2