



- NOTES:
- 1. INDICATOR CLIP, BOBBIN AND LABELS PACKED SEPARATELY.
 - 2. "X" - 1ST SUFFIX INDICATES THREAD TYPE: NONE - 1/2", S - 3/8"
 - 3. "X" - 2ND SUFFIX INDICATES CAP MATERIAL:
G - GRILAMID / RILSAN.
 - 4. "X" - 3RD SUFFIX INDICATES LANYARD CORD LENGTH:
40 - 4" / (10 cm)
50 - 5" / (13cm)
60 - 6" / (15cm)
114 - 11.4" / (28.9 cm)
 - 5. CRITICAL DIMENSIONS ARE CIRCLED AND SUBJECT TO INSPECTION
 - 6. DIMENSIONS IN PARENTHESES ARE FOR REFERENCE ONLY.
 - 7. ALL DIMENISONS ARE IN INCHES WITH NOMINAL IN METRIC BELOW.

TOOLING:	PART NO.	IFU:
----	----	IFU -V80040B

MOLDED PARTS:
GATES, PARTING LINES, AND FLASH PER QUALITY CRITERIA

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS SOLE PROPERTY OF HALKEY-ROBERTS CORPORATION ST. PETERSBURG, FL. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HALKEY-ROBERTS CORPORATION IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES:
ANGULAR: ± 1°
TWO PLACE DECIMAL ± .01
THREE PLACE DECIMAL ± .005

THIRD ANGLE PROJECTION

DRAWN BY
SJR

APPROVED BY
AK

MATERIAL

FINISH

DATE

DATE 8/28/2008

TITLE
HR® Halkey-Roberts®
ALPHA INFLATOR ENGLISH LANYARD

SIZE
A

SCALE
1:4

DRAWING NO.
CV90000XTXXB

REV
H

DO NOT SCALE DRAWING

SHEET
1 OF 1